


SIDECAR S PRO

“Sidecar is our most compact version of spotlights. It is a traditional side-by-side solution, inspired by the sidecar version of a motorcycle. We created a design that places the point of rotation on the track as central as possible to avoid a big offset from the track, allowing a number of spotlights to visually work well together. Developed and produced in Sweden”.

LED-spotlight with passive cooling system.
Die cast aluminium body, powder coat painted.
Integral heatsink. Integral premium driver.
Low ripple output current <4% to assure camera and scanner friendly performance.
Rotation 365°. Vertical adjustment +/- 90°.
Track mounted with 3-circuit adapter.



Class of protection	IP20, class I
Colours	White, black
Weight total	760g
Reflector	High purity aluminium
Lifetime	50.000h L80/B10 at Ta 25°C
Mounting	3-circuit universal adaptor
Voltage	220-240V 50/60hz
Qty per MCB	Max 34pcs/MCB 16A type B
Ripple out. current	< 4%. Flicker-free performance
Colour consistency	3 SDCM
Photobiological safety	RG1
Design	Jesper Ståhl
Dimming	Not dimmable



- White
- Black

SIDECAR S PRO

Description	Reflector	CCT (K)	CRI	Load	Lumen	Load	Lumen	Lm/W	○ White	● Black																																																																																																																		
LIGHTSOURCE						LUMINAIRE			ART. No.																																																																																																																			
WARM WHITE 3000K (930)																																																																																																																												
SIDECAR S Pro 2000lm SP 930	Spot 15°	3000K	92	16W	2280	19W	2110	110	213110	213114																																																																																																																		
SIDECAR S Pro 2000lm ME 930	Medium 25°	3000K	92	16W	2280	19W	2110	110	213111	213115																																																																																																																		
SIDECAR S Pro 2000lm FL 930	Flood 40°	3000K	92	16W	2280	19W	2110	110	213112	213116																																																																																																																		
SIDECAR S Pro 2000lm WFL 930	Widefl. 60°	3000K	92	16W	2280	19W	2020	106	213113	213117																																																																																																																		
SIDECAR S Pro 3000lm SP 930	Spot 15°	3000K	92	23W	3110	27W	2860	106	213210	213214																																																																																																																		
SIDECAR S Pro 3000lm ME 930	Medium 25°	3000K	92	23W	3110	27W	2860	106	213211	213215																																																																																																																		
SIDECAR S Pro 3000lm FL 930	Flood 40°	3000K	92	23W	3110	27W	2860	106	213212	213216																																																																																																																		
SIDECAR S Pro 3000lm WFL 930	Widefl. 60°	3000K	92	23W	3110	27W	2735	101	213213	213217																																																																																																																		
<table border="1"> <thead> <tr> <th colspan="4">Spot</th> <th colspan="4">Medium</th> <th colspan="4">Flood</th> <th colspan="4">Wideflood</th> </tr> <tr> <th colspan="2"></th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> <th colspan="2"></th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> <th colspan="2"></th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>13665</td> <td>18521</td> <td>1</td> <td>0,42</td> <td>7606</td> <td>10310</td> <td>1</td> <td>0,74</td> <td>4786</td> <td>6487</td> <td>1</td> <td>1,19</td> <td>2217</td> <td>3005</td> </tr> <tr> <td>2</td> <td>0,56</td> <td>3416</td> <td>4630</td> <td>2</td> <td>0,84</td> <td>1901</td> <td>2578</td> <td>2</td> <td>1,42</td> <td>1196</td> <td>1622</td> <td>2</td> <td>2,38</td> <td>554</td> <td>751</td> </tr> <tr> <td>3</td> <td>0,84</td> <td>1518</td> <td>2058</td> <td>3</td> <td>1,25</td> <td>845</td> <td>1146</td> <td>3</td> <td>2,18</td> <td>532</td> <td>721</td> <td>2,5</td> <td>2,97</td> <td>246</td> <td>334</td> </tr> <tr> <td>4</td> <td>1,12</td> <td>854</td> <td>1158</td> <td>4</td> <td>1,70</td> <td>475</td> <td>644</td> <td>4</td> <td>2,91</td> <td>299</td> <td>405</td> <td>3</td> <td>3,56</td> <td>139</td> <td>188</td> </tr> </tbody> </table>											Spot				Medium				Flood				Wideflood						2000lm		3000lm				2000lm		3000lm				2000lm		3000lm		m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	13665	18521	1	0,42	7606	10310	1	0,74	4786	6487	1	1,19	2217	3005	2	0,56	3416	4630	2	0,84	1901	2578	2	1,42	1196	1622	2	2,38	554	751	3	0,84	1518	2058	3	1,25	845	1146	3	2,18	532	721	2,5	2,97	246	334	4	1,12	854	1158	4	1,70	475	644	4	2,91	299	405	3	3,56	139	188
Spot				Medium				Flood				Wideflood																																																																																																																
		2000lm		3000lm				2000lm		3000lm				2000lm		3000lm																																																																																																												
m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																													
1	0,28	13665	18521	1	0,42	7606	10310	1	0,74	4786	6487	1	1,19	2217	3005																																																																																																													
2	0,56	3416	4630	2	0,84	1901	2578	2	1,42	1196	1622	2	2,38	554	751																																																																																																													
3	0,84	1518	2058	3	1,25	845	1146	3	2,18	532	721	2,5	2,97	246	334																																																																																																													
4	1,12	854	1158	4	1,70	475	644	4	2,91	299	405	3	3,56	139	188																																																																																																													
<p>3000K 930 Spectral power distributions</p>																																																																																																																												
NEUTRAL WHITE 4000K (940)																																																																																																																												
SIDECAR S Pro 2000lm SP 940	Spot 15°	4000K	92	16W	2460	19W	2280	119	213150	213154																																																																																																																		
SIDECAR S Pro 2000lm ME 940	Medium 25°	4000K	92	16W	2460	19W	2280	119	213151	213155																																																																																																																		
SIDECAR S Pro 2000lm FL 940	Flood 40°	4000K	92	16W	2460	19W	2280	119	213152	213156																																																																																																																		
SIDECAR S Pro 2000lm WFL 940	Widefl. 60°	4000K	92	16W	2460	19W	2190	114	213153	213157																																																																																																																		
SIDECAR S Pro 3000lm SP 940	Spot 15°	4000K	92	23W	3350	27W	3080	114	213250	213254																																																																																																																		
SIDECAR S Pro 3000lm ME 940	Medium 25°	4000K	92	23W	3350	27W	3080	114	213251	213255																																																																																																																		
SIDECAR S Pro 3000lm FL 940	Flood 40°	4000K	92	23W	3350	27W	3080	114	213252	213256																																																																																																																		
SIDECAR S Pro 3000lm WFL 940	Widefl. 60°	4000K	92	23W	3350	27W	2945	109	213253	213257																																																																																																																		
<table border="1"> <thead> <tr> <th colspan="4">Spot</th> <th colspan="4">Medium</th> <th colspan="4">Flood</th> <th colspan="4">Wideflood</th> </tr> <tr> <th colspan="2"></th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> <th colspan="2"></th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> <th colspan="2"></th> <th colspan="2">2000lm</th> <th colspan="2">3000lm</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,28</td> <td>14701</td> <td>19925</td> <td>1</td> <td>0,42</td> <td>8193</td> <td>11105</td> <td>1</td> <td>0,74</td> <td>5163</td> <td>6998</td> <td>1</td> <td>1,19</td> <td>2388</td> <td>3236</td> </tr> <tr> <td>2</td> <td>0,56</td> <td>3675</td> <td>4981</td> <td>2</td> <td>0,84</td> <td>2048</td> <td>2776</td> <td>2</td> <td>1,42</td> <td>1291</td> <td>1750</td> <td>2</td> <td>2,38</td> <td>597</td> <td>809</td> </tr> <tr> <td>3</td> <td>0,84</td> <td>1633</td> <td>2214</td> <td>3</td> <td>1,25</td> <td>910</td> <td>1234</td> <td>3</td> <td>2,18</td> <td>574</td> <td>778</td> <td>2,5</td> <td>2,97</td> <td>265</td> <td>360</td> </tr> <tr> <td>4</td> <td>1,12</td> <td>919</td> <td>1245</td> <td>4</td> <td>1,70</td> <td>512</td> <td>694</td> <td>4</td> <td>2,91</td> <td>323</td> <td>437</td> <td>3</td> <td>3,56</td> <td>149</td> <td>202</td> </tr> </tbody> </table>											Spot				Medium				Flood				Wideflood						2000lm		3000lm				2000lm		3000lm				2000lm		3000lm		m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	1	0,28	14701	19925	1	0,42	8193	11105	1	0,74	5163	6998	1	1,19	2388	3236	2	0,56	3675	4981	2	0,84	2048	2776	2	1,42	1291	1750	2	2,38	597	809	3	0,84	1633	2214	3	1,25	910	1234	3	2,18	574	778	2,5	2,97	265	360	4	1,12	919	1245	4	1,70	512	694	4	2,91	323	437	3	3,56	149	202
Spot				Medium				Flood				Wideflood																																																																																																																
		2000lm		3000lm				2000lm		3000lm				2000lm		3000lm																																																																																																												
m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux	m	∅	Lux	Lux																																																																																																													
1	0,28	14701	19925	1	0,42	8193	11105	1	0,74	5163	6998	1	1,19	2388	3236																																																																																																													
2	0,56	3675	4981	2	0,84	2048	2776	2	1,42	1291	1750	2	2,38	597	809																																																																																																													
3	0,84	1633	2214	3	1,25	910	1234	3	2,18	574	778	2,5	2,97	265	360																																																																																																													
4	1,12	919	1245	4	1,70	512	694	4	2,91	323	437	3	3,56	149	202																																																																																																													
<p>4000K 940 Spectral power distributions</p>																																																																																																																												

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/-150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.