


SIDECAR XS DIM

“Sidecar is our most compact version of spotlights. It is a traditional side-by-side solution, inspired by the sidecar version of a motorcycle. We created a design that places the point of rotation on the track as central as possible to avoid a big offset from the track, allowing a number of spotlights to visually work well together. Developed and produced in Sweden”.

LED-spotlight with passive cooling system.
Die cast aluminium body, powder coat painted.
Integral heatsink. Integral driver.
Dimmable via phase-cut.
Rotation 365°. Vertical adjustment +/- 90°.
Track mounted with 3-circuit adapter.



Class of protection	IP20, class I
Colours	White, black
Weight total	430g
Reflector	High purity aluminium
Lifetime	50.000h L80/B10 at Ta 25°C
Mounting	3-circuit universal adaptor
Voltage	220-240V 50/60hz
Qty per MCB	Max 50pcs/MCB 16A type B
Ripple out. current	< 20%
Colour consistency	3 SDCM
Photobiological safety	RG1
Design	Jesper Ståhl
Dimming	Phase-cut 100-20%



- White
- Black

SIDECAR XS DIM

Description	Reflector	CCT (K)	CRI	Load	Lumen	LIGHTSOURCE			LUMINAIRE		ART. No.																																				
						Load	Lumen	Lm/W	○ White	● Black																																					
WARM WHITE 2700K (927)																																															
SIDECAR XS Dim 1000lm ME 927 Medium 25°		2700K	92	8W	1090	10W	990	99			211121	211125																																			
SIDECAR XS Dim 1000lm FL 927 Flood 40°		2700K	92	8W	1090	10W	990	99			211122	211126																																			
<table border="1"> <thead> <tr> <th colspan="3">Medium 25°</th> <th colspan="3">Flood 40°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,44</td> <td>3900</td> <td>1</td> <td>0,70</td> <td>2117</td> </tr> <tr> <td>2</td> <td>0,88</td> <td>975</td> <td>2</td> <td>1,41</td> <td>529</td> </tr> <tr> <td>3</td> <td>1,32</td> <td>433</td> <td>3</td> <td>2,11</td> <td>235</td> </tr> <tr> <td>4</td> <td>1,76</td> <td>244</td> <td>4</td> <td>2,81</td> <td>132</td> </tr> </tbody> </table>						Medium 25°			Flood 40°			m	∅	Lux	m	∅	Lux	1	0,44	3900	1	0,70	2117	2	0,88	975	2	1,41	529	3	1,32	433	3	2,11	235	4	1,76	244	4	2,81	132	<p>2700K 927 Spectral power distributions</p>					
Medium 25°			Flood 40°																																												
m	∅	Lux	m	∅	Lux																																										
1	0,44	3900	1	0,70	2117																																										
2	0,88	975	2	1,41	529																																										
3	1,32	433	3	2,11	235																																										
4	1,76	244	4	2,81	132																																										
WARM WHITE 3000K (930)																																															
SIDECAR XS Dim 1000lm ME 930 Medium 25°		3000K	92	8W	1160	10W	1040	104			211111	211115																																			
SIDECAR XS Dim 1000lm FL 930 Flood 40°		3000K	92	8W	1160	10W	1040	104			211112	211116																																			
<table border="1"> <thead> <tr> <th colspan="3">Medium 25°</th> <th colspan="3">Flood 40°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,44</td> <td>4109</td> <td>1</td> <td>0,70</td> <td>2227</td> </tr> <tr> <td>2</td> <td>0,88</td> <td>1027</td> <td>2</td> <td>1,41</td> <td>557</td> </tr> <tr> <td>3</td> <td>1,32</td> <td>457</td> <td>3</td> <td>2,11</td> <td>247</td> </tr> <tr> <td>4</td> <td>1,76</td> <td>257</td> <td>4</td> <td>2,81</td> <td>139</td> </tr> </tbody> </table>						Medium 25°			Flood 40°			m	∅	Lux	m	∅	Lux	1	0,44	4109	1	0,70	2227	2	0,88	1027	2	1,41	557	3	1,32	457	3	2,11	247	4	1,76	257	4	2,81	139	<p>3000K 930 Spectral power distributions</p>					
Medium 25°			Flood 40°																																												
m	∅	Lux	m	∅	Lux																																										
1	0,44	4109	1	0,70	2227																																										
2	0,88	1027	2	1,41	557																																										
3	1,32	457	3	2,11	247																																										
4	1,76	257	4	2,81	139																																										
NEUTRAL WHITE 4000K (940)																																															
SIDECAR XS Dim 1000lm ME 940 Medium 25°		4000K	92	8W	1230	10W	1110	111			211151	211155																																			
SIDECAR XS Dim 1000lm FL 940 Flood 40°		4000K	92	8W	1230	10W	1110	111			211152	211156																																			
<table border="1"> <thead> <tr> <th colspan="3">Medium 25°</th> <th colspan="3">Flood 40°</th> </tr> <tr> <th>m</th> <th>∅</th> <th>Lux</th> <th>m</th> <th>∅</th> <th>Lux</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0,44</td> <td>4380</td> <td>1</td> <td>0,70</td> <td>2381</td> </tr> <tr> <td>2</td> <td>0,88</td> <td>1095</td> <td>2</td> <td>1,41</td> <td>595</td> </tr> <tr> <td>3</td> <td>1,32</td> <td>487</td> <td>3</td> <td>2,11</td> <td>265</td> </tr> <tr> <td>4</td> <td>1,76</td> <td>274</td> <td>4</td> <td>2,81</td> <td>149</td> </tr> </tbody> </table>						Medium 25°			Flood 40°			m	∅	Lux	m	∅	Lux	1	0,44	4380	1	0,70	2381	2	0,88	1095	2	1,41	595	3	1,32	487	3	2,11	265	4	1,76	274	4	2,81	149	<p>4000K 940 Spectral power distributions</p>					
Medium 25°			Flood 40°																																												
m	∅	Lux	m	∅	Lux																																										
1	0,44	4380	1	0,70	2381																																										
2	0,88	1095	2	1,41	595																																										
3	1,32	487	3	2,11	265																																										
4	1,76	274	4	2,81	149																																										

Luminous flux and connected electrical load are subject to an initial tolerance of +/- 5%. Tolerance of colour temperature: +/- 150 K. Tolerance of CRI +/- 1,5. Values apply to an ambient temperature of 25°C.